PAGE DE COUVERTURE DE LA FICHE DE DONNÉES DE SÉCURITÉ

révisé le: 20.11.2025

IDENTIFICATION DU PRODUIT:

Nom commercial: Autosol Motorrad Politur & Wachs

FOURNISSEUR QUI TRANSMET LA FICHE DE DONNÉES DE SÉCURITÉ:

SÜDO JASA AG Müslistrasse 89 9003 Spreitenbach Schweiz

Tel: +41 44 439 90 50

rei: +41 44 439 90 s sds@suedojasa.ch

Numéro d'urgence national: 145 (24h accessible, Tox Info Suisse, Zurich; pour les appels depuis la Suisse, renseignements en allemand, français et italien)

INFORMATIONS CONCERNANT LES UTILISATEURS:

Section 7 - Manipulation et stockage

Exigences suisses selon les directives CFST et les aide-mémoire SUVA:

Les exigences actuelles pour la manipulation et le stockage sont à consulter dans:

- Directives CFST pertinentes (p.ex. n° 1825 pour liquides inflammables)
- Aide-mémoire SUVA 11030 (Substances dangereuses Ce qu'il faut savoir)
- Aide-mémoire SUVA 44040 (Protection explosions lors de pulvérisation)
- Aide-mémoire SUVA spécifiques selon le type de substance

Disponible sous: www.suva.ch et www.cfst.admin.ch

Mesures de base:

- Documenter les instructions du personnel selon ChemG Art. 28
- Maintenir les contenants hermétiquement fermés
- Tenir éloigné des sources d'ignition pour produits inflammables
- Utiliser des locaux de stockage bien ventilés et secs

Section 8 - Contrôles de l'exposition et protection individuelle

Valeurs limites suisses:

Les valeurs VME et VLE actuellement valables pour tous les composants sont à consulter dans l'édition la plus récente des "Valeurs limites d'exposition aux postes de travail SUVA".

Disponible sous: www.suva.ch / Publications / Valeurs limites

Équipement de protection individuelle selon les directives SUVA:

- Gants de protection: Vérifier le matériau et les temps de perçage selon les spécifications du fabricant
- Protection oculaire: Lunettes de protection avec protection latérale selon EN 166
- Protection respiratoire: En cas de ventilation insuffisante selon la composition du produit
- Protection cutanée: Vêtements de protection en cas de risque de contact cutané

Mesures de protection détaillées: Aide-mémoire SUVA pertinents sur les EPI sous www.suva.ch

Section 13 - Considérations relatives à l'élimination

Élimination selon les dispositions suisses:

L'élimination appropriée doit être effectuée conformément à:

- Ordonnance sur la limitation et l'élimination des déchets (OLED)
- Ordonnance sur les mouvements de déchets (OMoD)
- Loi sur la protection des eaux (LEaux)

Dispositions actuelles sous: www.ofev.admin.ch / Déchets

Principes de base:

- Petites quantités (<5kg): Par les centres de collecte communaux pour déchets spéciaux
- Quantités commerciales: Par des entreprises d'élimination agréées OLED
- Emballages vides: Valorisables comme déchets d'emballage si complètement vidés
- Ne pas déverser dans les égouts ou les eaux

Code de déchet: Voir le répertoire actuel des déchets (OFEV) ou consulter un éliminateur agréé OLED

Section 15 - Informations réglementaires

Dispositions suisses pertinentes:

Ce produit est soumis à diverses dispositions réglementaires suisses. Les dispositions actuellement valables sont à consulter sous:

- ORRChim (Ordonnance sur la réduction des risques liés aux produits chimiques): www.admin.ch
- OPair (Ordonnance sur la protection de l'air): www.admin.ch
- OPAM (Ordonnance sur la protection contre les accidents majeurs): www.admin.ch
- Dispositions de protection du travail: www.seco.admin.ch
- Protection de la maternité/protection des jeunes travailleurs: www.seco.admin.ch

Observer les obligations de déclaration selon ORRChim Art. 26 lors de la mise sur le marché >100 kg/an.

Des prescriptions supplémentaires spécifiques à la branche peuvent être applicables.

Page de couverture créée: 20.11.2025 - SÜDO JASA AG Müslistrasse 43 CH-8957 Spreitenbach +41 44 439 90 50 sds@suedojasa.ch

Remarque: Cette page de couverture renvoie aux dispositions suisses actuellement en vigueur. Les utilisateurs sont tenus de s'informer sur les prescriptions actuellement valables et de les respecter.





1/1 Rowe Street, Freshwater NSW 2096 PO Box 309, Freshwater NSW 2096 (02) 9905 8400, Fax (02) 9905 8355

www.autosol.com.au

customerservice@autosol.com.au

A.B.N. 96 063 067 649

Section 1 - Identification of The Material and Supplier

Chemical nature: Blend of ingredients.

Trade Name: AUTOSOL® Motorbike Polish & Wax

Product Code/s: 1080

Product Use: Polishing preparation.

Creation Date: August, 2015

This version issued: July, 2025 and is valid for 5 years from this date.

Poisons Information Centre: Phone 13 1126 from anywhere in Australia

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Xi, Irritating. Hazardous according to the criteria of SWA.

Not a Dangerous Good according to Australian Dangerous Goods (ADG) Code, IATA or IMDG/IMSBC criteria.

Risk Phrases: R41, R37/38. Risk of serious damage to eyes. Irritating to respiratory system and skin.

Safety Phrases: S22, S23, S38, S51, S62, S24/25, S36/37. Do not breathe dust. Do not breathe vapours. In case of insufficient ventilation, wear suitable respiratory equipment. Use only in well ventilated areas. If swallowed, do not induce vomiting: seek medical advice immediately and show this SDS. Avoid contact with skin and eyes. Wear suitable protective clothing and gloves.

SUSMP Classification: None allocated.

ADG Classification: None allocated. Not a Dangerous Good according to Australian Dangerous Goods (ADG)

Code, IATA or IMDG/IMSBC criteria.

UN Number: None allocated



GHS Signal word: WARNING

HAZARD STATEMENT:

H315: Causes skin irritation.

H319: Causes serious eye irritation.

PREVENTION

P102: Keep out of reach of children.

P262: Do not get in eyes, on skin, or on clothing.

P264: Wash contacted areas thoroughly after handling.

P271: Use only outdoors or in a well ventilated area.

P281: Use personal protective equipment as required.

RESPONSE

P312: Call a POISON CENTRE or doctor if you feel unwell.

P362: Take off contaminated clothing and wash before reuse.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313: If skin irritation occurs: Get medical advice.

P337+P313: If eye irritation persists: Get medical advice.

P370+P378: In case of fire, use carbon dioxide, dry chemical, foam.

STORAGE

P402+P404: Store in a dry place. Store in a closed container.

P403+P235: Store in a well-ventilated place. Keep cool.

SAFETY DATA SHEET

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

Issued by: CMS International Pty Ltd Phone: (02) 99

Phone: (02) 9905 8400 (business hours)

Product Name: AUTOSOL® Motorbike Polish & Wax

Page: 2 of 5

This revision issued: July, 2025

DISPOSAL

P501: Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

Emergency Overview

Physical Description & Colour: White pasty solid.

Odour: Characteristic odour.

Major Health Hazards: may cause serious damage to eyes, irritating to respiratory system and skin, possible

respiratory tract irritant.

Potential Health Effects

Inhalation

Short Term Exposure This product is an inhalation irritant. Symptoms may include headache,

> irritation of nose and throat and increased secretion of mucous in the nose and throat. Other symptoms may also become evident, but they should

disappear after exposure has ceased if treatment is prompt.

Long Term Exposure

No data for health effects associated with long term inhalation.

Skin Contact

Short Term Exposure Available data indicates that this product is not harmful. It should present no

hazards in normal use. However product may be irritating, but is unlikely to

No data for health effects associated with long term skin exposure.

cause anything more than mild transient discomfort.

Long Term Exposure

Eye Contact

Short Term Exposure This product is a severe eye irritant. Symptoms may include stinging and

> reddening of eyes and watering which may become copious. Other symptoms such as swelling of eyelids and blurred vision may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment is likely to cause

permanent damage.

Long Term Exposure No data for health effects associated with long term eye exposure.

Ingestion

Short Term Exposure Significant oral exposure is considered to be unlikely. However, this product

is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all

should disappear once exposure has ceased.

Long Term Exposure

No data for health effects associated with long term ingestion.

Carcinogen Status

SWA No significant ingredient is classified as carcinogenic by SWA. NTP No significant ingredient is classified as carcinogenic by NTP. **IARC**

No significant ingredient is classified as carcinogenic by IARC.

Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc,%	TWA (mg/m ³)	STEL (mg/m³)
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	10-25	not set	not set
Kaolin clay	1332-58-7	10-25	10	not set
Distillates (petroleum), hydrotreated light	64742-47-8	10-25	not set	not set
2-Diethylaminoethanol	100-37-8	1-10	48	not set
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

SAFETY DATA SHEET

Issued by: CMS International Pty Ltd

Phone: (02) 9905 8400 (business hours)

Product Name: AUTOSOL® Motorbike Polish & Wax Page: 3 of 5

This revision issued: July, 2025

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: If irritation occurs, contact a Poisons Information Centre, or call a doctor. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. In severe cases, symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

Skin Contact: Gently brush away excess particles. Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 5 minutes or until chemical is removed.

Eye Contact: Quickly and gently brush particles from eyes. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is no risk of an explosion from this product under normal circumstances if it is involved in a fire.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: In case of fire, use carbon dioxide, dry chemical, foam.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade.

Flash point: >100°C
Upper Flammability Limit: No data.
Lower Flammability Limit: No data.
Autoignition temperature: No data.

Flammability Class: Not flammable (GHS); C1 combustible (AS 1940)

Section 6 - Accidental Release Measures

Accidental release: This product is sold in small packages, and the accidental release from one of these is not usually a cause for concern. For minor spills, clean up, rinsing to sewer and put empty container in garbage. Although no special protective clothing is normally necessary because of occasional minor contact with this product, it is good practice to wear impermeable gloves when handling chemical products. In the event of a major spill, prevent spillage from entering drains or water courses and call emergency services.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: Make sure that containers of this product are kept tightly closed. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure LimitsTWA (mg/m³)STEL (mg/m³)Kaolin clay10not set2-Diethylaminoethanol48not set

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

SAFETY DATA SHEET

Issued by: CMS International Pty Ltd Phone: (02) 9905 8400 (business hours)

Product Name: AUTOSOL® Motorbike Polish & Wax Page: 4 of 5

This revision issued: July, 2025

Ventilation: This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

Eye Protection: Protective glasses or goggles must be worn when this product is being used. Failure to protect your eyes may lead to severe harm to them or to general health. Emergency eye wash facilities must also be available in an area close to where this product is being used.

Skin Protection: You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: nitrile. **Respirator:** If there is a significant chance that dusts are likely to build up in the area where this product is being used, we recommend that you use a suitable dust mask.

Eyebaths or eyewash stations and safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

Section 9 - Physical and Chemical Properties:

Physical Description & colour: White pasty solid. Characteristic odour.

Boiling Point: Not available.

Freezing/Melting Point: No specific data. Paste at normal temperatures.

Volatiles: No data.
Vapour Pressure: No data.
Vapour Density: Not applicable.

Specific Gravity: 1.1

Water Solubility: Some, but not all ingredients are soluble.

pH: 8.5 (as supplied, 20°C)

Volatility: No data.

Odour Threshold: No data.

Evaporation Rate: Not applicable.

Coeff Oil/water Distribution: No data

Viscosity: No applicable.

Autoignition temp: No data.

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: Keep containers tightly closed. **Incompatibilities:** No particular Incompatibilities.

Fire Decomposition: Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. May form nitrogen and its compounds, and under some circumstances, oxides of nitrogen. Occasionally hydrogen cyanide gas in reducing atmospheres. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product will not undergo polymerisation reactions.

Section 11 - Toxicological Information

Local Effects:

Target Organs: There is no data to hand indicating any particular target organs.

Classification of Hazardous Ingredients

Ingredient Risk Phrases

2-diethylaminoethanol >=5%Conc<10%: Xi; R36/37/38

Section 12 - Ecological Information

Insufficient data to be sure of status.

SAFETY DATA SHEET

Product Name: AUTOSOL® Motorbike Polish & Wax Page: 5 of 5

This revision issued: July, 2025

Section 13 - Disposal Considerations

Disposal: Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

Section 14 - Transport Information

UN Number: This product is not classified as a Dangerous Good by ADG, IATA or IMDG/IMSBC criteria. No special transport conditions are necessary unless required by other regulations.

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations. The following ingredients: Naphtha (petroleum), hydrodesulfurized heavy, Distillates (petroleum), hydrotreated light, (both as liquid hydrocarbons) are mentioned in the SUSMP.

Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition)

AICS

Australian Inventory of Chemical Substances

SWA

Safe Work Australia, formerly ASCC and NOHSC

CAS number

Chemical Abstracts Service Registry Number

Hazchem Code Emergency action code of numbers and letters that provide information to emergency

services especially firefighters

IARC International Agency for Research on Cancer

NOS Not otherwise specified

NTP National Toxicology Program (USA)

R-Phrase Risk Phrase

SUSMP Standard for the Uniform Scheduling of Medicines & Poisons

UN Number United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous

Chemicals - Code of Practice" (December 2011) Copyright © Kilford & Kilford Pty Ltd, July, 2025. http://www.kilford.com.au/ Phone (02)9251 4532