



DELTALED SERIES

R65 LED Beacons

The Delta Series R65 LED Beacon range are designed and tested to agricultural and construction vehicle manufacturers specifications, utilising the solid state, maintenance free long life nature of LED technology and offering R65 flash patterns. This high performance range is robust and compact in a popular housing design and is available in six standard mounting options. This range of beacons is suitable for a variety of vehicles including large vehicles, refuse trucks, recovery, fleets and highway maintenance.

Models

PART NO.	VOLTAGE	LEDs	WATTS	MOUNT
DB5001A	12-24	12	18	3 Bolt
DB5002A	12-24	12	18	1 Bolt
DB5003A	12-24	12	18	DIN Pole
DB5004A	12-24	12	18	Magnetic
DB5006A	12-24	12	18	Flexi Pole
DB5007A	12-24	12	18	Flexi 1 Bolt

Flash Patterns

NO.	DESCRIPTION	PHASE	OTHER
0	Steady Burn 10% Duty Cycle	N/A	
1	125 SFPM (Single Flashes per minute)	A	ECE R65 Approved
2	125 SFPM (Single Flashes per minute)	B	ECE R65 Approved
3	125 DFPM (Double Flashes per minute)	A	ECE R65 Approved
4	125 DFPM (Double Flashes per minute)	B	ECE R65 Approved
5	125 TFPM (Triple Flashes per minute)	A	ECE R65 Approved
6	125 TFPM (Triple Flashes per minute)	B	ECE R65 Approved
7	125 QFPM (Quad Flashes per minute)	A	ECE R65 Approved
8	125 QFPM (Quad Flashes per minute)	B	ECE R65 Approved

Features and Benefits

- Polycarbonate lens and ABS Base
- Long life LED technology
- Operating Voltage Range 10-36V
- Current Consumption: 1.5 amps @ 12V
0.75 amps @ 24V
- 360° light output
- R65 Approved
- R10 Approved
- IP65 Rated

Dimensions

