

PRODUCT DATA SHEET

XTK8 EXACT X-LOCK

TOP LINE

- Lifetime
- Cutting ability for solid material
- Cutting ability for thin-walled material

Shape 42




- Precise cut, less force required
- Minimum bur formation for less rework
- Cool cut reduces tarnish colours and material distortion

The 0.8 mm cutting disc with ultra low-noise operation. Produces a precise and nearly burr-free cut.



Specially designed for low-power machines and battery-powered angle grinders



Type designation	XTK8 EXACT X-LOCK
Article designation 1	Extra-thin cutting disc
Article designation 2	X-LOCK
Article no.	211320
GTIN	4011890124567
Content	25
Content unit	Piece
Weight	0,029 kg
Product dimensions	125 x 0,8 x 22,23
Diameter 1	125 mm
Thickness	0,8 mm
Hole	22,23 mm
Shape long version	Depressed cutting disc
Shape short version	Shape 42
Working speed	80 m/s
Maximum revolutions	12250 U/min
Material suitability	Stainless steel Steel
Machine suitability	Freehand angle grinder
Technologies	BRAINTOOLS HYDROPROTECT EXTRATHIN
Safety and application identification	Iron and sulphur free ≤ 0,1%
Industry suitability of the article	Plant construction Building filter's shop Boiler and tank construction Vehicle construction Structural steel construction Foundry and dressing shop Pipeline construction Container construction Shipyards
Abrasive marking according to EN 12413	A60U9BF1433
Product category number	PK01
Product category text	XTS
GTIN barcode packing unit	4011890124604
Type of packaging	Carton
Packing unit	1
Package length	130 mm
Package width	130 mm
Package height	55 mm
Weight of packing unit	0,725 kg
Customs tariff number	68042218
Country of origin	DE

RHODIUS Schleifwerkzeuge GmbH & Co. KG

Brohltalstraße 2 · D-56659 Burgbrohl · service@rhodius.de · www.rhodius-abrasives.com
Tel. +49 2636 920-400 · kostenfreie Fax-Nr. (DE) +49 800 6645394

RHODIUS