

DECKBLATT ZUM SICHERHEITSDATENBLATT

überarbeitet am: 20.11.2025

PRODUKTIDENTIFIKATION:

Handelsname: Carsystem Silicone Remover Mild

LIEFERANT, DER DAS SICHERHEITSDATENBLATT ÜBERMITTELT:

SÜDO JASA AG

Müslistrasse 311

9225 Spreitenbach

Schweiz

Tel: +41 44 439 90 50

sds@suedojasa.ch

Nationale Notfallnummer: 145 (24h erreichbar, Tox Info Suisse, Zürich; für Anrufe aus der Schweiz, Auskünfte auf Deutsch, Französisch und Italienisch)

INFORMATIONEN FÜR DIE VERWENDER BETREFFEND:

Abschnitt 7 - Handhabung und Lagerung

Schweizerische Anforderungen gemäß EKAS-Richtlinien und SUVA-Merkblättern:

Die aktuellen Anforderungen für Handhabung und Lagerung sind zu entnehmen aus:

- Relevante EKAS-Richtlinien (z.B. Nr. 1825 für brennbare Flüssigkeiten)
- SUVA-Merkblatt 11030 (Gefährliche Stoffe - Was man darüber wissen muss)
- SUVA-Merkblatt 44040 (Explosionsschutz bei Spritzarbeiten, falls zutreffend)
- Produktspezifische SUVA-Merkblätter je nach Stoffart

Verfügbar unter: www.suva.ch und www.ekas.admin.ch

Grundlegende Maßnahmen:

- Mitarbeiterunterweisungen nach ChemG Art. 28 dokumentieren
- Behälter dicht verschlossen halten
- Von Zündquellen fernhalten bei brennbaren Produkten
- Gut belüftete, trockene Lagerräume verwenden

Abschnitt 8 - Begrenzung und Überwachung der Exposition

Schweizerische Grenzwerte:

Die aktuell gültigen MAK- und KZGW-Werte für alle Inhaltsstoffe sind der aktuellen Ausgabe "SUVA Grenzwerte am Arbeitsplatz" zu entnehmen.

Verfügbar unter: www.suva.ch / Publikationen / Grenzwerte

Persönliche Schutzausrüstung nach SUVA-Richtlinien:

- Schutzhandschuhe: Material und Durchbruchzeiten gemäß Herstellerangaben
- Augenschutz: Schutzbrille mit Seitenschutz gemäß EN 166
- Atemschutz: Bei unzureichender Belüftung entsprechend Produktzusammensetzung
- Hautschutz: Schutzkleidung bei Hautkontaktgefahr

Abschnitt 13 - Hinweise zur Entsorgung

Entsorgung nach schweizerischen Bestimmungen:

Die ordnungsgemäße Entsorgung ist durchzuführen gemäß:

- Verordnung über die Vermeidung und die Entsorgung von Abfällen (VVEA)
- Verordnung über den Verkehr mit Abfällen (VeVA)
- Gewässerschutzgesetz (GSchG)

Aktuelle Bestimmungen unter: www.bafu.admin.ch / Abfall

Grundprinzipien:

- Kleinmengen (<5kg): Über kommunale Sammelstellen für Sonderabfall
- Gewerbliche Mengen: Durch VeVA-bewilligte Entsorgungsunternehmen
- Leere Gebinde: Als Verpackungsabfall verwertbar, wenn vollständig entleert
- Nicht in Kanalisation oder Gewässer einleiten

Abfallcode: Siehe aktuelles Abfallverzeichnis (BAFU) oder VeVA-bewilligten Entsorger konsultieren

Abschnitt 15 - Rechtsvorschriften

Relevante schweizerische Bestimmungen:

Dieses Produkt unterliegt verschiedenen schweizerischen Rechtsvorschriften. Die aktuell gültigen Bestimmungen sind zu konsultieren unter:

- ChemRRV (Chemikalien-Risikoreduktions-Verordnung): www.admin.ch
- LRV (Luftreinhalte-Verordnung): www.admin.ch
- StFV (Störfall-Verordnung): www.admin.ch
- Arbeitsschutzbestimmungen: www.seco.admin.ch
- Mutterschutz/Jugendarbeitsschutz: www.seco.admin.ch

Meldepflichten nach ChemRRV Art. 26 bei Inverkehrbringen >100 kg/Jahr beachten.

Zusätzliche branchenspezifische Vorschriften können anwendbar sein.

Deckblatt erstellt: 20.11.2025 - SÜDO JASA AG Müslistrasse 43 CH-8957 Spreitenbach +41 44 439 90 50 sds@suedojasa.ch

Hinweis: Dieses Deckblatt verweist auf die jeweils aktuellen schweizerischen Bestimmungen. Verwender sind verpflichtet, sich über die aktuell gültigen Vorschriften zu informieren und diese einzuhalten.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 22.11.2024
2.3	13.05.2025	Date of first issue: 02.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	: Carsystem Silicone Remover Mild
Product code	: 147.023

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- stance/Mixture	: Cleaning agent, Degreasing agent Solvent
Recommended restrictions on use	: Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company	: Vosschemie GmbH Esinger Steinweg 50 25436 Uetersen Germany info@vosschemie.de
Telephone	: 04122 717 0
Telefax	: 04122 717158
Responsible Department	: Laboratory 04122 717 0 sds@vosschemie.de

1.4 Emergency telephone

Telephone	: Giftinformationszentrum (GIZ)-Nord, Göttingen, Deutschland 0551 19240
-----------	---

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version
2.3

DE / EN

Revision Date:
13.05.2025

Date of last issue: 22.11.2024
Date of first issue: 02.08.2022

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2

Specific target organ toxicity - single exposure, Category 3, Central nervous system

Aspiration hazard, Category 1

Long-term (chronic) aquatic hazard, Category 2

H225: Highly flammable liquid and vapor.

H336: May cause drowsiness or dizziness.

H304: May be fatal if swallowed and enters airways.

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

:



Signal Word

:

Danger

Hazard Statements

:

H225
H304
H336
H411

Highly flammable liquid and vapor.
May be fatal if swallowed and enters airways.
May cause drowsiness or dizziness.
Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements

:

EUH066

Repeated exposure may cause skin dryness or cracking.

Precautionary Statements

:

Prevention:

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261

Avoid breathing mist or vapors.

P271

Use only outdoors or in a well-ventilated area.

Response:

P301 + P310

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331

Do NOT induce vomiting.

Disposal:

P501

Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

Hazardous ingredients which must be listed on the label:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version

2.3

DE / EN

Revision Date:

13.05.2025

Date of last issue: 22.11.2024

Date of first issue: 02.08.2022

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

reaction mass of ethylbenzene and m-xylene and p-xylene

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Not Assigned 920-750-0 01-2119473851-33	Flam. Liq. 2; H225 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 25 - < 50
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not Assigned 927-241-2 01-2119471843-32	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 EUH066	>= 25 - < 50
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not Assigned 919-857-5 01-2119463258-33	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 EUH066	>= 1 - < 5

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version
2.3

DE / EN

Revision Date:
13.05.2025

Date of last issue: 22.11.2024
Date of first issue: 02.08.2022

reaction mass of ethylbenzene and m-xylene and p-xylene	Not Assigned 905-562-9 01-2119555267-33	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412 specific concentration limit STOT RE 2 ≥ 10 %	≥ 1 - < 5
Hydrocarbons, C9, Aromatics	Not Assigned 918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	≥ 1 - < 2,5
ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-2119475103-46	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	≥ 0,1 - < 5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : Symptoms of poisoning may appear several hours later.
First aider needs to protect himself.
Remove from exposure, lie down.
Take off all contaminated clothing immediately.
- If inhaled : Remove to fresh air.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 22.11.2024
2.3	13.05.2025	Date of first issue: 02.08.2022

DE / EN

- | | | |
|-------------------------|---|---|
| In case of skin contact | : | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
If symptoms persist, call a physician. |
| In case of eye contact | : | In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Protect unharmed eye.
If symptoms persist, call a physician. |
| If swallowed | : | Do NOT induce vomiting.
Get medical attention immediately.
If a person vomits when lying on his back, place him in the recovery position. |

4.2 Most important symptoms and effects, both acute and delayed

- | | | |
|-------|---|--|
| Risks | : | May be fatal if swallowed and enters airways.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking. |
|-------|---|--|

4.3 Indication of any immediate medical attention and special treatment needed

- | | | |
|-----------|---|------------------------|
| Treatment | : | Treat symptomatically. |
|-----------|---|------------------------|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | | |
|--------------------------------|---|---|
| Suitable extinguishing media | : | Carbon dioxide (CO ₂)
Dry powder
Alcohol-resistant foam |
| Unsuitable extinguishing media | : | Water
High volume water jet |

5.2 Special hazards arising from the substance or mixture

- | | | |
|---------------------------------------|---|--|
| Specific hazards during fire fighting | : | May form explosive mixtures in air.
Build-up of dangerous/toxic fumes possible in cases of fire/high temperature. |
| Hazardous combustion products | : | Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). |

5.3 Advice for firefighters

- | | | |
|--|---|---|
| Special protective equipment for fire-fighters | : | Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment. |
| Specific extinguishing methods | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 22.11.2024
2.3	13.05.2025	Date of first issue: 02.08.2022

DE / EN

Further information : In the event of fire and/or explosion do not breathe fumes.
Use a water spray to cool fully closed containers.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Ensure adequate ventilation, especially in confined areas.
Remove all sources of ignition.
Avoid contact with skin and eyes.
Wear personal protective equipment.
Evacuate personnel to safe areas.

6.2 Environmental precautions

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
Non-sparking tools should be used.
Shovel into suitable container for disposal.

Do not flush with water.

6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Local/Total ventilation : Ensure adequate ventilation.
Advice on safe handling : Avoid formation of aerosol.
Keep container closed when not in use.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapors or spray mist.
Avoid contact with skin and eyes.

Advice on protection against fire and explosion : Vapors may form explosive mixtures with air. Vapors are heavier than air and may spread along floors. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version 2.3 DE / EN Revision Date: 13.05.2025 Date of last issue: 22.11.2024
Date of first issue: 02.08.2022

Hygiene measures : When using do not eat, drink or smoke. Take off all contaminated clothing immediately.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Store in cool place. Keep in an area equipped with solvent resistant flooring.

Keep containers tightly closed in a dry, cool and well-ventilated place.

Further information on storage conditions : Keep away from heat and sources of ignition. Keep away from direct sunlight.

Storage must be in accordance with the BetrSichV (Germany).

Advice on common storage : Keep away from food and drink.
Incompatible with oxidizing agents.

Storage class (TRGS 510) : 3

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not Assigned	AGW	300 mg/m ³	DE TRGS 900
Peak-limit category: 2;(II)				
Further information: Group exposure limit for hydrocarbon solvent mixtures				
ethyl acetate	141-78-6	STEL	400 ppm 1.468 mg/m ³	2017/164/EU
Further information: Indicative				
		TWA	200 ppm 734 mg/m ³	2017/164/EU
Further information: Indicative				
		AGW	200 ppm 730 mg/m ³	DE TRGS 900
Peak-limit category: 2;(I)				
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
		MAK	200 ppm 750 mg/m ³	DE DFG MAK
Further information: Damage to the embryo or foetus is unlikely when the				

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version
2.3

DE / EN

Revision Date:
13.05.2025

Date of last issue: 22.11.2024
Date of first issue: 02.08.2022

MAK value or the BAT value is observed

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Routes of exposure	Potential health effects	Value
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Workers	Inhalation	Long-term systemic effects	2035 mg/m ³
	Workers	Skin contact	Long-term systemic effects	773 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	608 mg/m ³
	Consumers	Skin contact, Oral	Long-term systemic effects	699 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	871 mg/m ³
	Workers	Skin contact	Long-term systemic effects	77 mg/kg bw/day
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Consumers	Inhalation	Long-term systemic effects	185 mg/m ³
	Consumers	Skin contact, Oral	Long-term systemic effects	46 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	871 mg/m ³
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Consumers	Inhalation	Long-term systemic effects	185 mg/m ³
	Workers	Inhalation	Long-term systemic effects	151 mg/m ³
	Workers	Skin contact	Long-term systemic effects	12,5 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	32 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	7,5 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	7,5 mg/kg bw/day
ethyl acetate	Workers	Inhalation	Long-term systemic effects, Long-term local effects	734 mg/m ³
	Workers	Inhalation	Acute systemic effects, Acute local effects	1468 mg/m ³
	Workers	Skin contact	Long-term systemic effects	63 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects, Long-term local effects	367 mg/m ³
	Consumers	Inhalation	Acute systemic ef-	734 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version
2.3

DE / EN

Revision Date:
13.05.2025

Date of last issue: 22.11.2024
Date of first issue: 02.08.2022

			fects, Acute local effects	
	Consumers	Skin contact	Long-term systemic effects	37 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	4,5 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
ethyl acetate	Oral (Secondary Poisoning)	200 mg/kg food

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166
Hand protection
Material : Nitrile rubber
Glove thickness : $\geq 0,8$ mm
Guideline : DIN EN 374

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Preventive skin protection
Avoid natural rubber gloves.

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.
Long sleeved clothing

Respiratory protection : In case of inadequate ventilation wear respiratory protection.
Apply technical measures to comply with the occupational exposure limits.
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).

Filter type : Combined particulates and organic vapor type (A-P)

Protective measures : Avoid contact with the skin and the eyes.
Avoid contact with skin and clothing.
Handle in accordance with good industrial hygiene and safety practice.
Follow the skin protection plan.

Keep away from food, drink and animal feedingstuffs.

Environmental exposure controls

Soil : Avoid subsoil penetration.
Water : Do not flush into surface water or sanitary sewer system.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 22.11.2024
2.3	13.05.2025	Date of first issue: 02.08.2022

DE / EN

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: liquid
Color	: colorless
Odor	: characteristic
Melting point/freezing point	: not determined
Boiling point/boiling range	: 70 °C
Upper explosion limit / Upper flammability limit	: 11,5 %(V)
Lower explosion limit / Lower flammability limit	: 0,7 %(V)
Flash point	: 18 °C
Autoignition temperature	: not determined
pH	: Not applicable substance/mixture is non-soluble (in water)
Viscosity	
Viscosity, dynamic	: not determined
Viscosity, kinematic	: < 20,5 mm ² /s (40 °C)
Solubility(ies)	
Water solubility	: immiscible
Partition coefficient: n-octanol/water	: No data available
Vapor pressure	: 98 hPa (20 °C)
Density	: 0,74 - 0,75 g/cm ³ (20 °C)

9.2 Other information

Explosives	: Not explosive In use, may form flammable/explosive vapour-air mixture.
Self-ignition	: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 22.11.2024
2.3 DE / EN	13.05.2025	Date of first issue: 02.08.2022

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if used as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapors may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Extremes of temperature and direct sunlight.
Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Acute oral toxicity : LD50 Oral (Rat): > 5.840 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 23,3 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.800 - 3.100 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 22.11.2024
2.3	13.05.2025	Date of first issue: 02.08.2022

DE / EN

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Acute oral toxicity	: LD50 Oral (Rat): > 15.000 mg/kg Method: OECD Test Guideline 423
Acute inhalation toxicity	: LC50 (Rat): > 4,951 mg/l Exposure time: 4 h Test atmosphere: vapor Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 5.000 mg/kg Method: OECD Test Guideline 402

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Acute oral toxicity	: LD50 Oral (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	: LC50 (Rat): > 9,3 mg/l Exposure time: 4 h Test atmosphere: vapor Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	: LD50 Dermal (Rat): > 5.000 mg/kg Method: OECD Test Guideline 402

reaction mass of ethylbenzene and m-xylene and p-xylene:

Acute oral toxicity	: LD50 Oral (Rat): 3.523 - 4.000 mg/kg Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)
Acute inhalation toxicity	: LC50 (Rat, male): 6350 - 6700 ppm Exposure time: 4 h Test atmosphere: vapor Method: Regulation (EC) No. 440/2008, Annex, B.2
Acute dermal toxicity	: LD50 Dermal (Rabbit): 12.126 mg/kg

Hydrocarbons, C9, Aromatics:

Acute oral toxicity	: LD50 Oral (Rat, female): ca. 3.492 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	: LC50 (Rat): > 6,193 mg/l Exposure time: 4 h Test atmosphere: vapor Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 22.11.2024
2.3	13.05.2025	Date of first issue: 02.08.2022

DE / EN

Acute dermal toxicity : LD50 Dermal (Rabbit): > 3.160 mg/kg
Method: OECD Test Guideline 402

ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 4.934 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC0 (Rat): 22,5 mg/l, > 6000 ppm
Exposure time: 6 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20.000 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Assessment : Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Result : Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Assessment : Repeated exposure may cause skin dryness or cracking.

reaction mass of ethylbenzene and m-xylene and p-xylene:

Result : Skin irritation

Hydrocarbons, C9, Aromatics:

Result : Repeated exposure may cause skin dryness or cracking.

ethyl acetate:

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified due to lack of data.

Components:

reaction mass of ethylbenzene and m-xylene and p-xylene:

Result : Moderate eye irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 22.11.2024
2.3	13.05.2025	Date of first issue: 02.08.2022

ethyl acetate:

Species	: Rabbit
Result	: Moderate eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.

Respiratory sensitization

Not classified due to lack of data.

Components:

ethyl acetate:

Test Type	: Maximization Test
Routes of exposure	: Dermal
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: Did not cause sensitization on laboratory animals.

Germ cell mutagenicity

Not classified due to lack of data.

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Germ cell mutagenicity- Assessment	: Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)
------------------------------------	--

Hydrocarbons, C9, Aromatics:

Germ cell mutagenicity- Assessment	: Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)
------------------------------------	--

ethyl acetate:

Genotoxicity in vitro	: Test Type: Chromosome aberration test in vitro Test system: Chinese hamster ovary cells Method: OECD Test Guideline 473 Result: negative
-----------------------	---

Genotoxicity in vivo	: Test Type: Chromosomal aberration Species: Chinese hamster Method: OECD Test Guideline 474 Result: negative
----------------------	--

Germ cell mutagenicity- Assessment	: In vitro tests did not show mutagenic effects, In vivo tests did not show mutagenic effects
------------------------------------	---

Carcinogenicity

Not classified due to lack of data.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version
2.3

DE / EN

Revision Date:
13.05.2025

Date of last issue: 22.11.2024
Date of first issue: 02.08.2022

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Carcinogenicity - Assessment : Carcinogenicity classification not possible from current data.

Hydrocarbons, C9, Aromatics:

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

ethyl acetate:

Carcinogenicity - Assessment : Animal testing did not show any carcinogenic effects., Carcinogenicity classification not possible from current data.

Reproductive toxicity

Not classified due to lack of data.

Components:

ethyl acetate:

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity

STOT-single exposure

May cause drowsiness or dizziness.

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Assessment : May cause drowsiness or dizziness.

reaction mass of ethylbenzene and m-xylene and p-xylene:

Assessment : May cause respiratory irritation.

Hydrocarbons, C9, Aromatics:

Assessment : May cause respiratory irritation., May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version
2.3

DE / EN

Revision Date:
13.05.2025

Date of last issue: 22.11.2024
Date of first issue: 02.08.2022

ethyl acetate:

Target Organs : Central nervous system
Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified due to lack of data.

Components:

reaction mass of ethylbenzene and m-xylene and p-xylene:

Assessment : May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

May be fatal if swallowed and enters airways.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

May be fatal if swallowed and enters airways.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

May be fatal if swallowed and enters airways.

reaction mass of ethylbenzene and m-xylene and p-xylene:

May be fatal if swallowed and enters airways.

Hydrocarbons, C9, Aromatics:

May be fatal if swallowed and enters airways.

ethyl acetate:

No aspiration toxicity classification

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version
2.3

DE / EN

Revision Date:
13.05.2025

Date of last issue: 22.11.2024
Date of first issue: 02.08.2022

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 3 - 10 mg/l
End point: mortality
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): 4,6 - 10 mg/l
aquatic invertebrates
End point: Immobilization
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EL50 (Pseudokirchneriella subcapitata (green algae)): 10 - 30
plants
mg/l
End point: Growth rate
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox- : NOELR: 0,574 mg/l
icity)
Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other : NOELR: 1 mg/l
aquatic invertebrates (Chron-
ic toxicity)
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - < 30 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 22 - < 46 mg/l
aquatic invertebrates
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000
plants
mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox- : NOELR: 0,182 mg/l
icity)
Exposure time: 28 d

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 22.11.2024
2.3	13.05.2025	Date of first issue: 02.08.2022

DE / EN

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 0,317 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1.000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR: 0,131 mg/l
Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 0,23 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

reaction mass of ethylbenzene and m-xylene and p-xylene:

Toxicity to fish : LC50 (Fish): 2,6 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia dubia (Water flea)): 1 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202

EC50 (Daphnia dubia (Water flea)): 165 mg/l
Exposure time: 24 h

Toxicity to algae/aquatic plants : EC50 (algae): 2,2 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 22.11.2024
2.3	13.05.2025	Date of first issue: 02.08.2022

DE / EN

Method: OECD Test Guideline 201

IC50 (algae): 1 - 10 mg/l
Exposure time: 72 h

Toxicity to microorganisms : EC50 (Bacteria): 1 - 10 mg/l

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Hydrocarbons, C9, Aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 9,2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): 3,2 mg/l
aquatic invertebrates End point: Immobilization
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : NOELR (Pseudokirchneriella subcapitata (green algae)): 1
plants mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to daphnia and other : NOELR: 2,144 mg/l
aquatic invertebrates (Chronic toxicity) Exposure time: 21 d
Species: Daphnia magna (Water flea)

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

ethyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 230 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 610 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : NOEC (Desmodesmus subspicatus (green algae)): > 100 mg/l
plants Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC (Pseudomonas putida): 650 mg/l
Exposure time: 16 h

Toxicity to fish (Chronic toxicity) : NOEC: > 9,65 mg/l
Exposure time: 32 d
Species: Pimephales promelas (fathead minnow)
Method: OECD Test Guideline 210

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 22.11.2024
2.3	13.05.2025	Date of first issue: 02.08.2022

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 2,4 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

12.2 Persistence and degradability

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 98 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 89 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 28 d

Hydrocarbons, C9, Aromatics:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 78 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

ethyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 79 %
Related to: Biochemical oxygen demand
Exposure time: 20 d
Method: OECD Test Guideline 301D

12.3 Bioaccumulative potential

Components:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Partition coefficient: n-octanol/water : Remarks: No data available

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Partition coefficient: n- : log Pow: > 4

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 22.11.2024
2.3	13.05.2025	Date of first issue: 02.08.2022

DE / EN

octanol/water

reaction mass of ethylbenzene and m-xylene and p-xylene:

Partition coefficient: n-
octanol/water : log Pow: 3,2 (20 °C)

ethyl acetate:

Partition coefficient: n-
octanol/water : log Pow: 0,68 (25 °C)

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	: Do not dispose of with domestic refuse. Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Packaging that is not properly emptied must be disposed of as the unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal.
Waste Code	: The following Waste Codes are only suggestions: 14 06 03, other solvents and solvent mixtures

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version
2.3

DE / EN

Revision Date:
13.05.2025

Date of last issue: 22.11.2024
Date of first issue: 02.08.2022

08 01 11, waste paint and varnish containing organic solvents
or other hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN	:	UN 1263
ADR	:	UN 1263
RID	:	UN 1263
IMDG	:	UN 1263
IATA	:	UN 1263

14.2 UN proper shipping name

ADN	:	PAINT (naphtha (petroleum), hydrotreated light, Hydrocarbons, C9, Aromatics)
ADR	:	PAINT (naphtha (petroleum), hydrotreated light, Hydrocarbons, C9, Aromatics)
RID	:	PAINT (naphtha (petroleum), hydrotreated light, Hydrocarbons, C9, Aromatics)
IMDG	:	PAINT (naphtha (petroleum), hydrotreated light, Hydrocarbons, C9, Aromatics)
IATA	:	Paint (naphtha (petroleum), hydrotreated light, Hydrocarbons, C9, Aromatics)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	:	3
ADR	:	3
RID	:	3
IMDG	:	3
IATA	:	3

14.4 Packing group

ADN Packing group	:	II
----------------------	---	----

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version		Revision Date:	Date of last issue: 22.11.2024
2.3	DE / EN	13.05.2025	Date of first issue: 02.08.2022

Classification Code : F1
Hazard Identification Number : 33
Labels : 3

ADR

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)

RID

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

IMDG

Packing group : II
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 364
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 353
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 22.11.2024
2.3	13.05.2025	Date of first issue: 02.08.2022

DE / EN

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

E2 ENVIRONMENTAL HAZARDS

Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2004/42/EC
Volatile organic compounds (VOC) content: < 850 g/l
VOC content for the product in a ready to use condition.

Regulation (EC) No. 648/2004, as amended : 30 % and more: Aliphatic hydrocarbons
5 % or over but less than 15 %: Aromatic hydrocarbons
Allergens:
benzyl alcohol
benzyl benzoate

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

SAFETY DATA SHEET

VOSSCHEMIE

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 22.11.2024
2.3	13.05.2025	Date of first issue: 02.08.2022

DE / EN

SECTION 16: Other information

Full text of H-Statements

H225	: Highly flammable liquid and vapor.
H226	: Flammable liquid and vapor.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2017/164/EU	: Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
DE DFG MAK	: Germany. MAK BAT Annex IIa
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
2017/164/EU / STEL	: Short term exposure limit
2017/164/EU / TWA	: Limit Value - eight hours
DE DFG MAK / MAK	: MAK value
DE TRGS 900 / AGW	: Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization;

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

VOSSCHEMIE

Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 22.11.2024
2.3	13.05.2025	Date of first issue: 02.08.2022

DE / EN

KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 2	H225
STOT SE 3	H336
Asp. Tox. 1	H304
Aquatic Chronic 2	H411

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN