



MULTI FLOW

MULTI FLOW

POLYESTER MULTI-LEICHTSPACHTEL
POLYESTER MULTI LIGHT PUTTY



EXPERIENCE.
INNOVATION.
QUALITY.

MULTI FLOW

Art.-Nr.	Beschreibung <i>Description</i>	KP <i>SP</i>	VE <i>MOQ</i>	EAN Code
160.378	Multi Flow inkl. Härter KG 1,0	1 St./pcs.	6 St./pcs.	4102871603789
160.363	Multi Flow inkl. Härter KG 3,3	232 St./pcs.	232 St./pcs.	4102871603635

BESCHREIBUNG

- Sehr leichte Polyester Multifunktionspachtelmasse
- Selbstverlaufende, porenfreie Oberfläche
- Farbe: Hellblau

TROCKNUNGSZEIT

- 20 – 30 Minuten bei 18 – 20 °C Raum- und Objekttemperatur

EINSATZGEBIET

- Zum Füllen von kleinen bis mittleren Unebenheiten, Kratzern und Schleifspuren

VORTEILE

- Haftung auf gängigen Metalluntergründen, Holz, GFK und 2K Polyesterspachtel
- Sehr glatte, porenfreie Oberflächenergebnisse
- Selbstverlaufende Eigenschaften
- Sehr leicht schleifbar

DESCRIPTION

- Very light polyester multifunctional putty
- Self-levelling, non-porous surface
- Colour: Light-blue

DRYING TIME

- 20 – 30 minutes at 18 – 20 °C room- and objecttemperature

AREA OF APPLICATION

- For filling small and medium imperfections and scratches

BENEFITS

- Multi adhesion on common metal surfaces, wood, GRP and 2-comp. polyester putty
- Very smooth and pore-free surface results
- Self-levelling properties
- Very easy to sand



CARSYSTEM HEADQUARTERS
VOSSCHEMIE GmbH
Esinger Steinweg 50 | 25436 Uetersen / Germany

E-Mail: info@vosschemie.de
Tel.: +49 (0) 41 22 / 717-0 | Fax: +49 (0) 41 22 / 717-193

   www.carsystem.org